

Evaluation of the influence of mechanical pruning in the performance of the Row-Side Continuous Canopy Shaking Harvester Prototype

A. B. Dias¹, J. Falcão², A. Pinheiro¹, J. Peça¹

¹ MED – Mediterranean Institute for Agriculture, Environment and Development & Departamento de Engenharia Rural, Escola de Ciências e Tecnologia, University of Évora, Évora, Portugal;

² Torre das Figueiras Sociedade Agrícola Lda, Herdade da Torre das Figueiras, Monforte, Portugal.

Contact: adias@uevora.pt



Introduction, context and objectives

In high density olive orchards, mechanical harvesting is made by trunk shaking requiring a high demand of manual labour. The use of over-the-row grape harvesters is not available in these groves due to large canopies dimension. The row-side canopy harvester principle imposes fewer limitations on tree growth. Authors developed a prototype of a Row-Side Continuous Canopy Shaking Harvester - RSCSSH (Peça *et al.*, 2014). In a previous trial, the RSCSSH prototype had obtained an harvesting efficiency ranging between 70% and 76% of yield, without differences between the pruning treatments tested (Dias *et al.*, 2020). The objective of this trial was the evaluation of different mechanical pruning solutions in the efficiency of the RSCSSH prototype.

Mat & Methods

Tab.1 Olive orchard

Site	Variety	Irrigation	Plantation date	Array
Torre de Figueiras (39° 03' 34" N; 07° 28' 22" W)	Picual	Drip	1996	7m x 3.5 m

Tab. 2 Experimental design

Experimental design	Replications	Pruning block size
Completely randomised design	3	30 trees

Equipment



Fig. 1 "Topping" with disc-saw pruning machine



Fig. 2 "Hedging" with disc-saw pruning machine



Fig. 3 Manual pruning complement on the side faces of the canopy



Fig. 4 Side view of RSCSSH prototype



Fig. 5 RSCSSH prototype units working

Treatments

Tab. 3 Sequence of pruning interventions by treatment


Treatment	2015	2016	2017	2018
1				
2				
3	 Manual compl.		 Manual compl.	

Legend: Manual compl. – manual pruning complement

topping + hedging 2 faces of canopy; topping + hedging 2 faces of canopy

Note:
Topping: 2015 - at 3.5m high; 2017 – at 3.3m high;
Hedging: T1 – at 1.4 m from tree trunk;
T2 – at 1.0 m from tree trunk;
T3 – at 1.0 m from tree trunk.


Results



Legend: Th_ap – tree height after pruning; Th_es – tree height in early spring; Th_bh – tree height before harvest

Columns with the same letter are not significantly different - Duncan test at $P \leq 0,05$

Fig. 6 Average tree height by treatment



Legend: Cw_ap – canopy width after pruning; Cw_es – canopy width in early spring; Cw_bh – canopy width before harvest

Columns with the same letter are not significantly different - Duncan test at $P \leq 0,05$

Fig. 7 Average canopy width by treatment

Tab. 4 Olive yield per tree from 2015 until 2018 (kg tree⁻¹)

Treatment	2015	2016	2017	2018	Average by treatment
T1	25.4 a	24.7 a	14.7 a	27.8 a	23.5 A
T2	20.2 b	26.1 a	15.5 a	30.5 a	23.1 A
T3	23.4 ab	28.1 a	14.9 a	29.9 a	23.7 A
Average by year	22.9 C	26.3 B	15.1 D	29.4 A	23.4

Significant differences ($P \leq 0.05$) between years in olive yield

On average, no significant differences ($P > 0.05$) between treatments

Tab. 5 Harvester efficiency from 2015 until 2018 (%)

Treatment	2015	2016	2017	2018	Average by treatment
T1	84.9 a	86.9 a	77.2 a	77.2 a	81.6 A
T2	81.0 a	84.1 a	75.5 a	76.6 a	79.3 A
T3	79.1 ab	82.4 a	78.4 a	79.1 a	79.7 A
Average by year	81.7 A	84.5 A	77.0 B	76.6 B	80.0

Harvester efficiency:

Significant differences ($P \leq 0.05$) between years:

- differences in the RSCSSH working parameters;
- differences in the canopy dimension.

No significant differences between treatments ($P > 0.05$).

Conclusions and perspectives

Adequacy of olive canopy to RSCSSH prototype should consist on:

- topping below the upper limit of vibratory rotor (3.6 m);
 - hedging the two faces of canopy with higher intensity (for example at 1.0m from tree trunk);
 - remove exposed wood stumps on the sides of the canopy, manually; all in the first year;
- A second topping should be performed two years later to control tree height.

Evaluation of other olive canopy shapes in RSCSSH efficiency: hedge training system and "modified" vase shape

References: Dias et al. (2020) Front. Plant Sci. 10:1631; Peça et al. (2014) Acta Hort. 1057, 391-397

Acknowledgements : Torre das Figueiras Sociedade Agrícola Lda for the availability of technical and human resources. Ministry of Agriculture by financial support with the project PRODER entitled "Evaluation of the performance of the row-side continuous canopy harvesting machine", and the project PDR2020 entitled "Mechanized pruning and continuous harvesting of olive groves of Portuguese varieties".